

■ Calgary ☎ 403-248-8837 ■ Edmonton ☎ 780-435-2800 ■ London ☎ 519-672-5561 ■ Moncton ☎ 506-384-6101  
 ■ Montreal ☎ 450-655-6676 ■ Ottawa ☎ 613-741-4591 ■ Quebec ☎ 418-681-878801 ■ Saskatoon ☎ 306-651-2647  
 ■ Toronto ☎ 905-760-8211 ■ Vancouver ☎ 604-522-3944 ■ Winnipeg ☎ 204-694-2849

## SOPRASOLIN HD

**Description:** SOPRASOLIN HD is a multi-purpose self-adhesive membrane composed of SBS modified bitumen, self-protected by an aluminium sheet.  
 SOPRASOLIN HD is especially designed to waterproof details around vents, chimneys, skylights, ventilation units, etc. SOPRASOLIN HD is recommended for repair work and all general maintenance work. SOPRASOLIN HD is designed to be left exposed.

**Installation:**

1. Clean and dry the substrate.
2. Spread ELASTOCOL STICK primer and let dry.
3. Unroll, position and cut or shape the membrane to needed dimensions.
4. Pull out the silicone-coated film for 20 to 30 cm, and then adhere that portion on the substrate. Pull out the paper and stick the membrane.
5. Immediately after the installation, press the membrane firmly with a roller, to avoid any air pockets.

### Properties:

Properties	Standards	SOPRASOLIN HD
Thickness (mm)	-	1.0
Dimension (m)	-	1 x 10*
Colour	-	Aluminium
Top face	-	Aluminium sheet
Underface	-	Silicone release sheet
Breaking strength, MD/XD (kN/m)	CAN/CGSB-37.56-M 9 <sup>th</sup> draft	4.7 / 4.7
Ultimate elongation, MD/XD (%)	CAN/CGSB-37.56-M 9 <sup>th</sup> draft	210 / 210
Tear resistance, MD/XD (N)	CAN/CGSB-37.56-M 9 <sup>th</sup> draft	20 / 35

\* Cut rolls are available upon request.  
 (All values are nominal)



**NOTE: SOPREMA INC.** may modify the composition and/or utilisation of its products without prior notice. Consequently orders will be filled according to the latest specification.