



## SECTION I: PRODUCT INFORMATION

PRODUCT: SIKAFLEX® 15LM REVISION DATE: February 15, 2006

USE: ONE COMPONENT URETHANE BASED SEALANT

MANUFACTURER: SIKA CANADA INC.  
601, avenue Delmar  
Pointe Claire, QC  
H9R 4A9

**EMERGENCY TELEPHONE NUMBER: CANUTEC (collect) (613) 996-6666**

TDG CLASSIFICATION: Not Regulated WHMIS Classification: D2A  
UN NUMBER: Not Established Class: Not Applicable  
Packaging Group: Not Applicable

## SECTION II: HAZARDOUS INGREDIENTS

Hazardous ingredients	%	T.L.V.	# CAS	LD <sub>50</sub> (species, route)	LC <sub>50</sub> (species, route)
CALCIUM OXIDE	1-5	Not Available	1305-78-8	Not Available	Not Available
XYLENE	1-5	100 ppm	1330-20-7	4300 (oral, rat)	6350 ppm/4h
POLYOL AND ISOCYANATE PREPOLYMER	15-40	Not Established	Not Available	Not Established	Not Established

## SECTION III: PHYSICAL CHARACTERISTICS

Physical State:	Paste	Boiling Point:	Not Established
Appearance and Odor:	Aromatic odor colored paste	Freezing Point:	Not Established
Odor Threshold:	Not Established	Density:	1,3 g/ml
Evaporation Rate:	Not Established	Water Solubility:	Not Established
Vapor Density:	Not Established	PH:	Not Established
Vapor Pressure:	Not Established	% volatile:	< 5
		Water/Oil Distribution:	Not Established



PRODUCT: SIKAFLEX® 15LM

**SECTION IV: FIRE AND EXPLOSION HAZARDS**

Flammability: Combustible  
If Yes, under what conditions: Flame, spark

Extinguishing methods: Foam, dry chemical products, CO<sub>2</sub>, water for large flames.

Special Methods: Firefighters must wear complete protective clothing with respiratory equipment and they must protect any exposed skin. Heated isocyanates react strongly with water.

TDG Flammability Class: Not Regulated  
Flammable upper limits (% vol.): Not Established  
Flammable lower limits (% vol.): Not Established  
Flash Point (method used): > 80° C (TCC)  
Auto-ignition temperature: Not Established  
Dangerous Combustion: Carbon oxides, Aldehydes, Ketones, HCL, Nitrogen Oxide, TDI, MDI

Protect from mechanical impact: No

Protect from static discharge: No

**SECTION V: REACTIVITY DATA**

Chemical stability: Yes  
If not, under what conditions

Incompatibility with other material: Yes  
If Yes, which ones: Acid, strong oxidizer, amine.

Dangerous decomposition products: Carbon oxides, Aldehydes, Ketones, HCL, Nitrogen Oxide, TDI, MDI

Polymerization Risks: No



PRODUCT: SIKAFLEX® 15LM

SECTION VI: TOXIC PROPERTIES

ROUTE OF ENTRY / CONTACT

Eyes: Irritating

Skin: Irritating  
Contact may result in dermatitis, allergic reactions, sensitization

Inhalation: Vapor or mist from this product may cause irritation.

Ingestion: May cause nausea, vomiting, diarrhea, gastro-intestinal system disorder, constipation.

Carcinogenicity: No

Toxic effects on reproduction: No

Teratogenicity: Xylene is classified as a development toxicant (Embryo toxin)

Mutagenicity: No

Product with synergistic effects: Not Established

Over exposure may cause breathing difficulties, sensitization, headaches, nausea, vomiting. May aggravate respiratory, skin, eye, lung problems and allergies.

If the product is applied according to the manufacturer, none of these symptoms should be encountered.

A person who is sensitized to isocyanate may have a reaction with a level of isocyanate well below the T.L.V.

Xylene is a central nervous system depressor and in rare cases, may cause a sensitization of the heart muscle causing arrhythmia.

An acute or chronic exposure will increase the toxic effects mentioned in this section and may aggravate respiratory problems. An over exposure may cause death.



PRODUCT: SIKAFLEX® 15LM

**SECTION VII: PREVENTIVE MEASURES**

**PERSONAL PROTECTIVE EQUIPMENT**

Gloves: Use chemical resistant gloves.

Respiratory equipment: Not necessary under normal use.

Eyes: Full-face mask or safety glasses

Shoes: Leather

Clothing: Rubber Apron

Other: Eye wash station, shower

**OTHERS**

Ventilation: Sufficient ventilation required

Procedure in case of leaks: Absorb with sand or other absorbent material.

Handling and Equipment methods: Avoid skin, eye and clothing contact

Warehouse Requirements: Keep all containers closed in a cool, dry and well ventilated area. Keep away from heat and open flame.

Special Shipping Instructions: See TDG class

Waste Disposal: Dispose of sand and rinse water according to municipal, provincial or federal laws for disposal of chemicals.



PRODUCT: SIKAFLEX® 15LM

**SECTION VIII: FIRST AID**

**Skin:** Remove contaminated clothing and shoes.  
Wash immediately with plenty of water.  
Wash clothing before re-wearing.  
Consult a physician if required.

**Eyes:** Rinse eyes immediately with plenty of water for several minutes, while holding eyelids wide open, to ensure a proper wash.  
See a physician immediately.

**Inhalation:** In the case of overexposure, evacuate to fresh air.  
Consult a physician if required.

**Ingestion:** Drink plenty of water. Do not induce vomiting.  
Do not give anything by mouth to an unconscious person.  
See a physician immediately.

**SECTION IX: PREPARATION INFORMATION**

Prepared by: Steve Gosselin  
Telephone #: (514) 697-2610  
Fax #: (514) 694-2792

**Notice To Reader**

*The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to any use and processing.*