

Fred S. Gage
Product Manager
Waterproofing and Deck Coatings

January 21, 2004

To: All Tremco Membrane Distributors and Dealers
From: Fred Gage
Re: **Addition of the Vulkem 250 GC SL Commercialization**

Due to the overwhelming response of the Vulkem 250 GC, Tremco has added another Vulkem 250 GC viscosity grade. The current Vulkem 250 GC will be labeled as Vulkem GC R (Rollable) for vertical, horizontal and cant bead applications. The new grade will be the Vulkem 250 GC SL (Self-Leveling) for horizontal surfaces. Both still can be applied to green or damp concrete 24 hours after forms have been removed, a huge time saving innovation.

Vulkem 250 GC SL is a self-leveling viscosity designed to apply quickly and easily to horizontal surfaces saving time and labor. The Vulkem 250 GC SL has the ability to level to a consistent 60 mils for standard application or up to 120 mils for high-build applications. For additional information on Tremco's Vulkem 250 GC High-Build System's please visit our website www.tremcosealants.com.

Tremco looks forward to continually working with our customers to offer the latest technology in our below-grade waterproofing package. This package now includes the most unique single component waterproofing membrane in the business with the Vulkem 250 GC, a complete line of drainage and protection courses, a full line of Paraseal bentonite sheet and a hot rubberized asphalt TREMproof 150.

The latest Vulkem 250 GC data sheet is available on our website www.tremcosealants.com.

If you have any further questions, please contact your local Tremco District Sales Manager or Technical Service Representative.

Thank you for your continued support.

Fred S Gage